Short Quotation Notice

Principal, ASPEE College of Horticulture & Forestry, N.A.U., Navsari-396450, invites quotations in sealed cover by post/courier within five days of publication of this advertisement for Repairing and Renovation for Onion dehydration plant building & fruit and vegetable processing building of this office. The detail specifications of repairing and renovation work along with terms and conditions would be available at the www.nau.in.

-Sd-

Principal, ACHF, NAU, Navsari

માહીતી/નવ/૫૪૦/૨૦૨૧

દૈનીક સમાચાર પત્ર 'સંદેશ' તારીખઃ ૧૬/૦૩/૨૦૨૧, સુરત આર્વતિ, પાન નંબર–૬

QUOTATION DOCUMENT

Dismantling tiles of stone floors laid in mortar including stacking of serviceable of unserviceable materials and disposal of unserviceable materials with all lead and lift.	It No.	Description	Qty	Rate	Per	Amount
steel) shutters including chowkhats architraves holdfasts and other attachment etc. complete and stacking them within all lead and lift (i) Not exceeding 3Sq.M. in area. 3 Demolition of brick work & stone masonry around door frame including stacking of serviceable materials & disposal of unserviceable materials with all lead and lift. (ii) in cement mortar. 4 Providing and fixing 24" x 24" vitrified tiles 8 mm thick tile flooring over 20 mm (average) base of cement mortar 1:6 (1 cement: 6 coarse sand) on new surface or fixing on existing flooring by adhesive material including dismantling of existing flooring and jointed with color cement slurry including finished with flush pointing & cleaning the surface etc. complete for Light shade (upto 10 ton) 5 Providing and fixing 35 mm thick teak wood shutters for Doors, and including Indian teak wood frames 10 cm x 7 cm. size including fixures and fastenings including primer coat of approved quality and two coats of oil pianting etc, complete. (ii) Fully Panelled included in each door; SS Aldrop& Tadi –(150-200 x 12 mm)-2.00 Nos., SS Handle – (100 mm)-2.00 Nos., SS Stopper-(150-200 mm)-1.00Nos., Hanging type door stopper-1.00Nos. and Hinges (4" x1"x1)-3.00Nos. 6 Brickwork Using common brunt clay Building brick having crushing Strength not less than 35 kg/Sq.Cm. in foundation and plinth In cement mortar 1:6 (1-Cement: 6-Fine sand) (B) Conventional 7 20 mm thick sand faced cement plaster on wall upto hight 10 metres above ground level consisting of 12mm thick backing coat of c.m. 1:3 (1 cement: 3 sand) and 8 mm thick finishing coat of c.m. 1:1 (1 cement: 1 sand) etc. complete. 8 Applying two coats and Primer of Birla (White Cement based) or asian (acrylic lapy-putty) or equivalent & two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. 9 Finishing wall with water proofing cement paint on wall surface (two	1	stacking of serviceable of unserviceable materials and			Smt.	
frame including stacking of serviceable materials & disposal of unserviceable materials with all lead and lift. (ii) in cement mortar. 4 Providing and fixing 24" x 24" vitrified tiles 8 mm thick tile flooring over 20 mm (average) base of cement mortar 1:6 (1 cement: 6 coarse sand) on new surface or fixing on existing flooring by adhesive material including dismantling of existing flooring and jointed with color cement slurry including finished with flush pointing & cleaning the surface etc. complete for Light shade (upto 10 ton) 5 Providing and fixing 35 mm thick teak wood shutters for Doors, and including Indian teak wood frames 10 cm x 7 cm. size including fixitures and fastenings including primer coat of approved quality and two coats of oil painting etc, complete. (ii) Fully Panelled included in each door; SS Aldrop& Tadi –(150-200 x 12 mm)-2.00 Nos., SS Handle – (100 mm)-2.00 Nos., SS Stopper-(150-200 mm)+1.00Nos., Hanging type door stopper-1.00Nos. and Hinges (4" x1"x1)-3.00Nos. 6 Brickwork Using common brunt clay Building brick having crushing Strength not less than 35 kg./Sq.Cm. in foundation and plinth In cement mortar 1:6 (1-Cement : 6-Fine sand) (B) Conventional 7 20 mm thick sand faced cement plaster on wall upto hight 10 metres above ground level consisting of 12mm thick backing coat of c.m. 1:3 (1 cement : 3 sand) and 8 mm thick finishing coat of c.m. 1:3 (1 cement : 3 sand) and 8 mm thick finishing coat of c.m. 1:1 (1 cement : 1 sand) etc. complete. 8 Applying two coats and Primer of Birla (White Cement based) or asian (acrylic lapy-putty) or equivalent & two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. 9 Finishing wall with water proofing cement paint on wall surface (two coats) to give an approved brand and manufactures and of required shape even shade after thoroughly brushing the surface to remove all dirt, and remains of lo	2	steel) shutters including chowkhats architraves holdfasts and other attachment etc. complete and stacking them	Nos		Nos	
tile flooring over 20 mm (average) base of cement mortar 1:6 (1 cement: 6 coarse sand) on new surface or fixing on existing flooring by adhesive material including dismantling of existing flooring and jointed with color cement slurry including finished with flush pointing & cleaning the surface etc. complete for Light shade (upto 10 ton) 5 Providing and fixing 35 mm thick teak wood shutters for Doors, and including Indian teak wood frames 10 cm x 7 cm. size including fixtures and fastenings including primer coat of approved quality and two coats of oil painting etc, complete. (ii) Fully Panelled included in each door; SS Aldrop& Tadi ~(150-200 x 12 mm)-2.00 Nos., SS Handle ~ (100 mm)-2.00 Nos., SS Stopper-(150-200 mm)-1.00Nos., Hanging type door stopper-1.00Nos. and Hinges (4" x1"x1)-3.00Nos. 6 Brickwork Using common brunt clay Building brick having crushing Strength not less than 35 kg./Sq.Cm. in foundation and plinth In cement mortar 1:6 (1-Cement: 6-Fine sand) (B) Conventional 7 20 mm thick sand faced cement plaster on wall upto hight 10 metres above ground level consisting of 12mm thick backing coat of c.m. 1:3 (1 cement: 3 sand) and 8 mm thick finishing coat of c.m. 1:3 (1 cement: 3 sand) and 8 mm thick finishing coat of c.m. 1:1 (1 cement: 1 sand) etc. complete. 8 Applying two coats and Primer of Birla (White Cement based) or asian (acrylic lapy-putty) or equivalent & two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. 9 Finishing wall with water proofing cement paint on wall surface (two coats) to give an approved brand and manufactures and of required shape even shade after thoroughly brushing the surface to remove all dirt, and remains of loose powdered material.	3	frame including stacking of serviceable materials & disposal of unserviceable materials with all lead and lift. (ii) in cement			Cmt	
Doors, and including Indian teak wood frames 10 cm x 7 cm. size including fixtures and fastenings including primer coat of approved quality and two coats of oil painting etc, complete. (ii) Fully Panelled included in each door; SS Aldrop& Tadi –(150-200 x 12 mm)-2.00 Nos., SS Handle – (100 mm)-2.00 Nos., SS Stopper-(150-200 mm)-1.00Nos., Hanging type door stopper-1.00Nos. and Hinges (4" x1"x1)-3.00Nos. Brickwork Using common brunt clay Building brick having crushing Strength not less than 35 kg./Sq.Cm. in foundation and plinth In cement mortar 1:6 (1-Cement: 6-Fine sand) (B) Conventional		tile flooring over 20 mm (average) base of cement mortar 1:6 (1 cement: 6 coarse sand) on new surface or fixing on existing flooring by adhesive material including dismantling of existing flooring and jointed with color cement slurry including finished with flush pointing & cleaning the surface etc. complete for Light shade (upto 10 ton)	Smt.			
crushing Strength not less than 35 kg./Sq.Cm. in foundation and plinth In cement mortar 1:6 (1-Cement : 6-Fine sand) (B) Conventional 7 20 mm thick sand faced cement plaster on wall upto hight 10 metres above ground level consisting of 12mm thick backing coat of c.m. 1:3 (1 cement : 3 sand) and 8 mm thick finishing coat of c.m. 1:1 (1 cement : 1 sand) etc. complete. 8 Applying two coats and Primer of Birla (White Cement based) or asian (acrylic lapy-putty) or equivalent & two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. 9 Finishing wall with water proofing cement paint on wall surface (two coats) to give an approved brand and manufactures and of required shape even shade after thoroughly brushing the surface to remove all dirt, and remains of loose powdered material.	5	Doors , and including Indian teak wood frames 10 cm x 7 cm. size including fixtures and fastenings including primer coat of approved quality and two coats of oil painting etc, complete. (ii) Fully Panelled included in each door; SS Aldrop& Tadi –(150-200 x 12 mm)-2.00 Nos., SS Handle – (100 mm)-2.00 Nos., SS Stopper-(150-200 mm)-1.00Nos., Hanging type door stopper-1.00Nos. and Hinges (4" x1"x1)-			Smt.	
7 20 mm thick sand faced cement plaster on wall upto hight 10 metres above ground level consisting of 12mm thick backing coat of c.m. 1:3 (1 cement : 3 sand) and 8 mm thick finishing coat of c.m. 1:1 (1 cement : 1 sand) etc. complete. 8 Applying two coats and Primer of Birla (White Cement based) or asian (acrylic lapy-putty) or equivalent & two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. 9 Finishing wall with water proofing cement paint on wall surface (two coats) to give an approved brand and manufactures and of required shape even shade after thoroughly brushing the surface to remove all dirt, and remains of loose powdered material.	6	crushing Strength not less than 35 kg./Sq.Cm. in foundation and plinth In cement mortar 1:6 (1-Cement: 6-Fine sand)			Cmt	
based) or asian (acrylic lapy-putty) or equivalent & two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. 9 Finishing wall with water proofing cement paint on wall surface (two coats) to give an approved brand and manufactures and of required shape even shade after thoroughly brushing the surface to remove all dirt, and remains of loose powdered material.		10 metres above ground level consisting of 12mm thick backing coat of c.m. 1:3 (1 cement : 3 sand) and 8 mm thick finishing coat of c.m. 1:1 (1 cement : 1 sand) etc. complete.	Smt.			
9 Finishing wall with water proofing cement paint on wall surface (two coats) to give an approved brand and manufactures and of required shape even shade after thoroughly brushing the surface to remove all dirt, and remains of loose powdered material.	8	based) or asian (acrylic lapy-putty) or equivalent & two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other			Smt.	
, I Diai 1/3.	9	Finishing wall with water proofing cement paint on wall surface (two coats) to give an approved brand and manufactures and of required shape even shade after thoroughly brushing the surface to remove all dirt, and			Smt.	

We agree to abide by the terms and conditions of supply mentioned in this quotation document.

DECLARATION

I/We solemnly declare that we have attached all the documents mentioned above and mentioned in the quotation. It is verified that all the certificates / permissions/ documents are valid and current as on date and have not been withdrawn / cancelled by the issuing authority.

I/We further undertake to produce on demand the original certificate / permission / document for verification at any stage during the processing of the quotation.

Name of the Firm: Signature of party

(With Stamp, Name & Designation)

ASPEE College of Horticulture and Forestry Navsari Agricultural University, Navsari

: TERMS AND CONDITIONS:

- 1. Sealed quotations are invited in the prescribed filled up form from reputed, reliable, experience and registered company or supplier of scheduled item(s).
- 2. The quotation in sealed cover/envelop should be super-scribed as <u>Quotations for PHTC</u> (12940) at the top of the cover.
- 3. The quotation document should be reach to the office of Principal, ASPEE College of Horticulture and Forestry, NAU, Navsari -396450 (Gujarat) positively during our office hours within five days of publication of the news paper advertisement.
- 4. The quoted price should be in **Indian Rupees only** inclusive of all taxes including GST etc and FOR delivery at the Onion Dehydration and Fruits and Vegetable Processing Plant building/College. It included Labor Cess and all relevant taxes.
- 5. Certificate of exemption of customs duty/excise duty will be supplied if required.
- 6. Security deposited @ 5% of total amount of quotation or Rs. 5735/- which ever is higher as Demand Draft should be submitted in favour of "AAO, ACHF, NAU, Navsari" along with sealed quotation
- 7. The name of specific of supply and repair and renovation work should be as mentioned above quotation document sheet.
- 8. Comprehensive onsite warranty for 1 year or more from the date of completion of the work items. Please clearly mention the parts, which are not covered under warranty, separately.
- 9. The payment will be released only after complete supply and successful completion of repair and renovation work at respective site.
- 10. ACHF, NAU, Navsari reserves the right to change any terms and condition even after inviting the quotations with/without prior notification.
- 11. In case of any dispute, final decision of The Principal, ASPEE College of Horticulture and Forestry, Navsari Agricultural University, Navsari 396 450, Gujarat will be binding to all. In case of any dispute with respect to this quotation call, a suit in that behalf shall be subject to Navsari Jurisdiction.

CERTIFICATE

- 1. I/we have gone through the above terms and conditions and agree to abide by the same.
- 2. I/we undertake to accept the interpretation of the above terms and conditions of the quotation document as decided by the competent authorities of ACHF, NAU, Navsari. One copy of this is being sent herewith.

Date:	SIGNATURE
Place:	(Name, Designation and seal of the party)